

09/125888
8-27-98



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B32B 27/06, 33/00, A61M 25/00, B65B 55/18		A1	(11) International Publication Number: WO 99/03677
			(43) International Publication Date: 28 January 1999 (28.01.99)
(21) International Application Number: PCT/SE98/01383 (22) International Filing Date: 13 July 1998 (13.07.98) (30) Priority Data: 9702748-6 18 July 1997 (18.07.97) SE (71) Applicant (for all designated States except US): ASTRA AKTIEBOLAG [SE/SE]; S-151 85 Södertälje (SE). (72) Inventors; and (75) Inventors/Applicants (for US only): PETTERSSON, Agneta [SE/SE]; Astra Tech AB, P.O. Box 14, S-431 21 Mölndal (SE). UTA, Jan [SE/SE]; Astra Tech AB, P.O. Box 14, S-431 21 Mölndal (SE). (74) Agent: ASTRA AKTIEBOLAG; Patent Dept., S-151 85 Södertälje (SE).			(81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report.
(54) Title: BARRIER MATERIAL			
(57) Abstract An assembly (10; 110) which has been exposed to ethylene oxide gas comprising an article (3; 103) sterilised by the ethylene oxide gas and a sealed container (6; 106) formed from a laminate having an inner layer which contains a polyolefin, an outer layer which contains a polyester, a polyolefin or a polyamide and an intermediate layer which contains a silicon oxide. The laminate acts to keep the ethylene oxide gas out of the container.			
			